

# MATERIAL SAFETY DATA SHEET CBT® 100 resin

### **SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

Cyclics Corporation 2135 Technology Drive Schenectady, NY 12308

PHONE NUMBERS: Emergency Information Non-Emergency Information

PRODUCT IDENTIFIER: PRODUCT DESCRIPTION: 518-881-1411 518-881-1411

CBT® 100 resin Poly (butylene terephthalate) cyclized. 1,4-Benzenedicarboxylic acid, dimethylester, polymer with 1, 4-butanediol, CAS #263244-54-8. May be used to produce molded articles or as a component of other industrial products.

PRODUCT USE:

## **SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS**

Components listed below are classified as hazardous as defined by the OSHA Hazard Communication Standard. The concentrations (expressed as weight percent) are typical or average values for this product. See also SECTION 15, REGULATORY INFORMATION.

| Component Name | % | CAS Number | OSHA PEL | ACGIH TWA |
|----------------|---|------------|----------|-----------|
| none           |   |            |          |           |

### **SECTION 3 - HAZARDS IDENTIFICATION**

| EMERGENCY OVERVIEW:   | Solid material that will burn in a fire creating dense, toxic smoke.   |
|---|--|
| HMIS RATING:<br>POTENTIAL HEALTH EFFECTS<br>INGESTION:<br>INHALATION:<br>SKIN CONTACT:<br>EYE CONTACT:<br>NOTE: | <ul> <li>Health 0, Flammability 1, Reactivity 0</li> <li>No known adverse effects.</li> <li>No known adverse effects.</li> <li>No known adverse effects.</li> <li>No known adverse effects.</li> <li>CBT resin may cause skin or eye irritation in some individuals due to abrasive action of the resin in powder or granular form.</li> </ul> |
| CHRONIC / CARCINOGENICITY<br>NTP:<br>OSHA:<br>IARC:   | Not tested<br>Not classified as a carcinogen<br>Not listed as a carcinogen   |

## **SECTION 4 - FIRST AID MEASURES**

| EYES:       | Flush eyes with a large amount of clean, room temperature water for up to 15 minutes. After initial flushing remove contact lenses. If irritation persists seek medical attention promptly. |
|-------------|---|
| SKIN:       | Remove contaminated clothing. Wash affected areas with soap and water. Seek medical attention if irritation persists.   |
| INGESTION:  | Not known to cause adverse health effects. Do not induce vomiting.  |
| INHALATION: | Not known to cause adverse health effects. Leave con-<br>taminated area and get fresh air.  |

### **SECTION 5 - FIRE FIGHTING MEASURES**

| FIRE FIGHTING:                 | Fight fire from a safe distance with proper personal<br>protective equipment including self-contained breathing<br>apparatus.   |
|--------------------------------|---|
| EXTINGUISHING MEDIA:           | Water spray, foam. Carbon dioxide and dry chemical are<br>not recommended because their lack of cooling capacity<br>may permit re-ignition.   |
| CONDITIONS OF FLAMMABILITY:    | Requires a continuous flame source to ignite.   |
| FLASH POINT:                   | None  |
| AUTOIGNITION TEMPERATURE:      | 380 C (680 F)   |
| EXPLOSION DATA:                | Material is not sensitive to mechanical impact, but finely<br>ground material is sensitive to static discharge under dust<br>cloud conditions. In limited testing with CBT resin dust<br>(-200 mesh), a minimum concentration of 35 gm/m3.<br>and minimum ignition energy of 0.4 joules were required to<br>form an explosive dust cloud. |
| EXPLOSION LIMITS:              | NA  |
| HAZARDOUS COMBUSTION PRODUCTS: | Intense heat, black smoke, carbon dioxide, carbon monoxide.   |
| SECTION 6 - ACCID              | ENTAL RELEASE MEASURES  |
| GENERAL:                       | Sweep up spillage and reuse or dispose, as appropriate.<br>Insure that molten resin has thoroughly cooled before<br>disposal.   |
| SECTION 7 - HAI                | NDLING AND STORAGE  |
| HANDLING:                      | Use good industrial hygiene practices and provide<br>adequate ventilation. Secondary operations on molded<br>parts (such as grinding sanding or sawing) could<br>produce an explosion hazard if dust is not adequately<br>controlled. Use adequate ventilation and aggressive   |

STORAGE:

housekeeping practices to prevent dust accumulation. Store resin on pallets in a cool dry covered area to maintain the integrity of the packing material. Do not stack more than two units high (pallets, drums, or boxes). Do not store in areas near open flame(s) or other potential ignition sources.

#### **SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

| ENGINEERING CONTROLS: | Fumes generated during thermal processing of<br>CBT resin may cause irritation in some individuals. |
|-----------------------|---|
|                       | Minimize exposures through controlled exhaust and fresh air makeup.                                 |
| PERSONAL PROTECTION:  |   |
| GENERAL:              | Grinding, sanding or sawing plastic parts can produce airborne particles.                           |
| EYE/FACE:             | Wear safety glasses with side shields or chemical goggles, as appropriate.                          |
| SKIN:                 | Avoid prolonged or unnecessary direct contact with resin granules/powder.                           |
| RESPIRATORY:          | Wear a well-fitting dust respirator if area ventilation is insufficient.                            |

#### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

| PHYSICAL STATE:                        | Solid                                      |                    |
|--|--|--------------------|
| ODOR AND APPEARANCE:                   | Off white plastic pellets/granules/powder. | Slight, mild odor. |
| MELTING POINT:                         | Melts between 120 – 200 C.                 | -                  |
| VAPOR PRESSURE (mm Hg):                | Nil  |                    |
| SPECIFIC GRAVITY (water=1):            | 1.3  |                    |
| WATER SOLUBILITY:                      | <0.3 ppm                                   |                    |
| % VOLATILES:                           | <1.0                                       |                    |
| EVAPORATION RATE:                      | Nil  |                    |
| OCTANOL / WATER PARTITION COEFFICIENT: | 3.52                                       |                    |

### **SECTION 10 - STABILITY AND REACTIVITY**

STABILITY: REACTIVITY:

CONDITIONS TO AVOID:

HAZARDOUS DECOMPOSITION PRODUCTS:

Stable. Not reactive under recommended conditions of handling and storage. Strong oxidizing agents. None. Hazardous polymerization will not occur.

#### **SECTION 11 - TOXICOLOGICAL INFORMATION**

ACUTE ORAL:

LD-50:greater than 5g/kg (rat), based on tests of similar material (poly- butylene terephthalate).

#### **SECTION 12 - ECOLOGICAL INFORMATION**

ECOLOGICAL INFORMATION:

This material is not known to be harmful to the environment. Decomposition is not expected to produce toxic waste products. This material facilitates the recycling and reuse of polyester resins. Plastic particles produced using this material can be recycled and used in the

### **SECTION 13 - DISPOSAL INFORMATION**

DISPOSAL:

This resin is not RCRA regulated hazardous waste. Recycling should always be considered as the first and most desirable option. If not recyclable, then dispose of in accordance with applicable local, state and federal regulations. See also Section 15 – Regulatory Information.

#### **SECTION 14 - TRANSPORTATION INFORMATION**

STATUS:

This resin is not classified as a hazardous material for transportation purposes.

#### **SECTION 15 - REGULATORY INFORMATION**

| TOXIC SUBSTANCES CONTROL ACT (TSCA) | CBT resin is listed on the public US TSCA Chemical Substance Inventory.  |
|-------------------------------------|--|
| SUPPLIER NOTIFICATION REQUIREMENTS: | As a new and innovative chemical, CBT is currently<br>regulated by the EPA/TSCA under the "Significant<br>New Use Rule" (SNUR). Obligations imposed by this<br>SNUR apply equally to all users. The SNUR specifically<br>requires that this material be stored, handled, pro-<br>cessed and disposed without a predictable or purposeful<br>release to surface waters. Please contact us directly if<br>you have questions regarding this requirement. |
| EU REGULATORY NOTIFICATION:         | As stated by Council Directive 92/32/EEC dated April 30, 1992, CBT resin is exempt from notification as a new substance in the European Union because it meets the definition of a polymer and is comprised solely of EINECS-listed monomers.  |

### **SECTION 16 - OTHER INFORMATION**

DISCLAIMER: This Material Safety data Sheet (MSDS) information is provided based on the requirements of Hazard Communication Regulations. Cyclics Corporation does not warrant the suitability for use of this MSDS for any other material or product not specifically identified herein. Cyclics Corporation does not warrant the accuracy or authenticity of this MSDS unless it was obtained directly from Cyclics Corporation, or posted or viewed on the Cyclics Corporation website. Modification of this MSDS, unless specifically authorized by Cyclics Corporation, is strictly prohibited. This MSDS is based on information which is believed to be reliable, but may be subject to change as new information becomes available. Since it is not possible to anticipate all conditions of use, additional safety precautions may be required. As the use of this material is not under Cyclics Corporation's control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. CYCLICS CORPORATION MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO THE MERCHANTABILITY OR FITNESS FOR A PARTICULAR APPLICATION OR PURPOSE.

#### PREPARED BY:

Robert Lindberg – Director, EHS

ABBREVIATIONS Revision Date: January 25, 2007 ACGIH: American Conference of Governmental Industrial Hygienists. CAS: Chemical Abstracts service HMIS: Hazardous Material Information System OSHA: Occupational Safety and Health Administration PEL: Permissible Exposure Limit PPE: Personal Protective Equipment TWA: Time Weighted Average

"Cyclics", "Cyclics Corporation", and "CBT" are registered trademarks of Cyclics Corporation in the United States and other countries.